




Ames Research Center
Aeronautical Test and Simulation Division

VIRTUAL SIMULATION LABORATORY


A DEMONSTRATOR PROJECT
FOR A VIRTUAL LABORATORY



Simulation Laboratories



Ames Research Center Aeronautical Test and Simulation Division





Ames Research Center
Aeronautical Test and Simulation Division

VIRTUAL SIMULATION LABORATORY

A DEMONSTRATOR PROJECT FOR A VIRTUAL LABORATORY

**A virtual environment providing remote,
interactive participation with ARC
simulation laboratories**




**Expedites delivery of
aeronautical knowledge
obtained from simulation
experiments to US aircraft industry**

**Leverage the information
technologies inherent to
real-time simulation to
create an immersive,
highly interactive, virtual
environment tailored to
the needs of the
aeronautical design
process**

**This project will deliver a fully functional prototype, situated at JSC,
participating in a Space Shuttle simulation on the VMS in FY97.**

**POC: Tom Alderete ext. 4-3271
Simulation Laboratories**



CENTRAL ROLE OF SIMULATION IN AIRCRAFT DESIGN CYCLE

- **Delivers NASA's simulation capability to industry's doorstep**
 - ARC simulators are high fidelity, research oriented facilities
 - ARC simulators can be used for specific, focused purposes as well as basic research topics
- **Allows industry to iterate design steps with piloted simulation**
 - faster, less expensive pilot-in-the-loop evaluation of designs
 - closes loop with CFD and WT testing for better design decisions earlier in the process
 - interoperability among AOS facilities such as ATC, SDTF, full mission, and part task
 - collaborative work with Neural Net simulations (Code I)
- **Enables industry/government partnerships to the benefit of US aeronautics**
 - easier access to National facilities
 - shared databases
 - more effective and efficient design process




Graphic of Virtual VMS Control Room



Graphic of Control Room and Motion System



3-D Virtual Environment with 2-D HUD Overlay



Strip Charts Added to Display

AIRSPEED : 294. kts
GRND SPD : 503. fps
MACH NUMBER : 0.48

ALTITUDE : 16. ft
ALT RATE : 14.99 fps

FLT PATH : -18.0 deg
A o A : 6.4 deg

WEIGHT : 233000. lbs.
X C G : 1075.7 inches.
MASS MOMENT : 1.88

RUN NUMBER : 111
THRESHOLD CROSSING HEIGHT : 23.0
X POSITION AT MG TD : 2358.0
Y POSITION AT MG TD : 0.1
EQIV AIRSPEED AT MG TD : 196.6 knots
ALT RATE AT MG TD : 2.2 fps
Y POSITION AT NG TD : 54.5
MAX PITCH RATE DURING SLAPDOWN : -9.83 deg / s
Y MAX DEVIATION ON RUNWAY : 55.7
MAX GEAR LOAD -- N : 201. L: 157881. R: 223333.
SPEED AT NG TD : 199.0 knots

Left Brake Energy

82.9

Left Side Energy

-0.4

Right Side Energy


19.4

Right Brake Energy

127.0

End of Run Display

SSV simulation plot #1



File=sample.rnd; Signal Suffix=[none]; Date=Feb 4, 1997 10:50:27


Page 1 of 2

X-Y Plotting Using Quickplot




Ames Research Center Aeronautical Test and Simulation Division

VLAB Systems Block Diagram





Ames Research Center Aeronautical Test and Simulation Division



VLAB Configuration at the Johnson Space Center (JSC)





Ames Research Center Aeronautical Test and Simulation Division




‘Teleresearcher’ at JSC

Simulation Laboratories




Research Test Plans

- **Baseline Performance**
- **Regular Performance Testing**
- **Latency vs. Realtime at VMS**
- **Evaluate Alternate Communications Methods**
- **Compare Different Operational Modes/
Procedures**
- **Evaluate Research Effectiveness with Different
Configurations**



Users Surveyed

- Rated VLAB as very useful and would use it again**
- Rated the virtual interface as very good**
- Liked the ability to customize the tools suite and views within the graphical user interface**
- Obtained “Needed Data” using VLAB**
- Rated performance and reliability as very good**
- Rated support as excellent**




Network Usage and Performance

- Maximum Net Usage Configuration per Functional Component**
 - Client @ < 1 Mbit/s**
 - Audio System @ < 1 Mbit/sec**
 - Video Conference @ 6 Mbit/sec**
 - Observation Video @ 15 Mbit/sec**
- Minimized Net Usage Configuration per Functional Component**
 - Client @ < 1 Mbit/s**
 - Audio System @ < 1 Mbit/sec**
 - Video Conference @ 2 Mbit/sec**
 - Observation Video @ 4.3 Mbit/sec**
- Network performance was reliable and consistent with two exceptions:**
 - Time lost troubleshooting ATM switch problem at JSC site**
 - Spurious disruption of audio/video UDP streams on two occasions**
 - No essential data lost at either event.**



Network Usage and Performance

VLAB Min vs Max Configuration Network Usage [UDP]





Summary


- **Tool Deemed Very Useful**
 - Remote & Local Investigators Collaborated with Colleagues at JSC to Solve Numerous Problems.
 - Investigator Ran Experiment an Extra Week from the Remote Site.
 - Other Programs are Inquiring About VLAB for their Application.



WHY DO IT?

CENTRAL ROLE OF SIMULATION IN AIRCRAFT DESIGN CYCLE

- **Delivers NASA's simulation capability to industry's doorstep**
 - ARC simulators are high fidelity, research oriented facilities
 - ARC simulators can be used for specific, focused purposes as well as basic research topics
- **Allows industry to iterate design steps with piloted simulation**
 - faster, less expensive pilot-in-the-loop evaluation of designs
 - closes loop with CFD and WT testing for better design decisions earlier in the process
 - interoperability among AOS facilities such as ATC, SDTF, full mission, and part task
 - collaborative work with Neural Net simulations (Code I)
- **Enables industry/government partnerships to the benefit of US aeronautics**
 - easier access to National facilities
 - shared databases
 - more effective and efficient design process



Ames Research Center
Aeronautical Test and Simulation Division

URL

- **<http://www.simlabs.arc.nasa.gov/vlab>**